



# **TRIO ALK-212**

## **PET COKE CLEANER**

**TRIO-ALK 212;** It is a concentrated product used for the cleaning of cargo warehouses after the discharge of pet-coke load.

### **PRODUCT FEATURES AND BENEFITS**

- It is certified according to IMO.
- It is a very effective product in pet-coke cleaning.
- Suitable for use in epoxy and stainless steel tanks.
- Aluminium is not suited for use in zinc alloy tanks.

### **DOSAGE AMOUNT AND INTENDED USE**

The dilution rate varies depending on the amount of contamination of the surface to be cleaned. Using the spraying equipment, the concentrated or 40-50% diluted solution is sprayed on the surface. Chemical must be applied from bottom to top. Application from top to bottom will cause chemical effect to decrease and stain.

**SPRAYING METHOD :** After the solution is applied to the surface, it should be allowed to react for 15-20 minutes (the surface should not be allowed to dry while waiting), rinse with water at 60-70° C if possible, starting from the bottom with the help of a high pressure water jet. If necessary, the process can be repeated by looking at the cleaning result. The final rinsing must be performed with fresh water to prevent salt residue on the surface.

**The phrases provided above are standard flushing procedures and the tank will vary depending on the physical condition of the warehouses and the type of load.**

**NOTE:** Please review the MSDS reports before use for safety, occupational health and safety.